



\$1.75

- Large Svea metal baffle to deflect heat from bottom of bulb keeping condensed mercury temperature in proper relation to ambient temperature.
- 2. Ideal tube temperature conditions and radiation protect filament life.
- 3. Deep cup anode of processed Svea metal, free from occluded gases.
- 4. Measured mercury pellet controls mercury volume. ABSENCE OF EXCESS MERCURY PREVENTS AMALGAMATION ON ELEMENTS AND GETTER. RESULTS: CLEAR BULB FOR RADIATION, LESS HEATING TIME DELAY.
- All UNITED 966 rectifiers are pre-shipment tested at 3200 volts DC to assure that they are Built to Take II.

UNITED ELECTRONICS COMPANY - 42 SPRING ST., NEWARK, N. J.



Type HFM

Mobile Crystal Control

for 5- and 10-Meter PHONE—CW—ICW and 20–40 Meter CW


- Single 40 meter crystal for all bands
- 10 Watts Carrier on 5 and 10 Meters
 15 watts on 20 and 40 meters
- Micalex insulated plug-in coils



TYPE TR-6A6
DUPLEX
TRANSMITTER
RECEIVER

\$39.75

SPECIAL EQUIP-MENT for ALL RE-QUIRE MENTS. Bulletin 37 will interest you. Write for it—it's FREE.



Type HFM CRYSTAL CONTROLLED MOBILE or FIXED TRANSMITTER. Complete with all coils \$48 net F.O.B.

Bliley LD2 Mounted Xtal \$4.80 extra

RADIO TRANSCEIVER LABORATORIES 8627 115th Street, Richmond Hill, N. Y.